

PRODUCT-DETAILS

776LR-Q5440-S 900 A ELBOW 15/25 KV



General Information	
Extended Product Type	776LR-Q5440-S
Product ID	7TAA122200R0013
EAN	5415022105742
Catalog Description	900 A ELBOW 15/25 KV
Long Description	900 Amp, 35kV, 600 Series Elbow with Test Point, with Insulated Plug, Cap, Stud, Lug and Cable Adapter. Cold-Shrinkable Jacket Seal Included. Cable Insulation Diameter 1.900 inch to 2.120 inch. Bi-Metal Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 1250. Cold-Shrinkable Jacket Seal Included.

Ordering	
5415022105742	
783786386048	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	10.5 in 267 mm	
Package Level 1 Height	4.38 in 111 mm	

Package Level 1 Depth / 13.25 in Length 337 mm

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20120306
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold Shrinkable Jacket Seal.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical	776LR-Q5440-S
Information	
Instructions and	776LR-Q5440-S
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly
Code (IGCC)	

Categories

776LR-Q5440-S 3

