

PRODUCT-DETAILS

## 755LR-J0230

## 35KV 600A DB ELBOW WO/TP J0230



General Information	
Extended Product Type	755LR-J0230
Product ID	7TAA122300R0016
EAN	0783786361663
Catalog Description	35KV 600A DB ELBOW WO/TP J0230
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded #1/ Compacted Solid 1/0 /mmSquared Compact 50.

Ordering		
0783786361663		
783786361663		
United States (US)		
8535908020		
each		

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	14 in 356 mm	
Package Level 1 Height	11.25 in 286 mm	

Package Level 1 Depth / 9.25 in Length 235 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	19990326
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 0.980 inch to 1.180 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical	755LR-J0230	
Information		

Instructions and 755LR-J0230 Manuals

## UNSPSC 39121421 WEEE Category Product Not in WEEE Scope IDEA Granular Category 4586 >> Electrical connector assembly Code (IGCC)

## **Categories**

755LR-J0230 3

