

PRODUCT-DETAILS

755LR-J0240

35KV 600A DB ELBOW WO/TP J0240



General Information	
Extended Product Type	755LR-J0240
Product ID	7TAA122300R0017
EAN	0783786640553
Catalog Description	35KV 600A DB ELBOW WO/TP J0240
Long Description	600 Amp, 35KV, Elbow with Insulated Plug, Cap, Stud, Lug and Cable Adapter, Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor

Ordering	
EAN	0783786640553
UPC	783786640553
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece

Additional Information

Connections to	High Voltage	Annaratus
Connections to	mian-voitade	Apparatus.

	connections to riight voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	19980108
Environmental	Fully Submersible
Conditions	
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 0.980 inch to 1.180 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755LR-J0240
Instructions and Manuals	755LR-J0240

Classifications

UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category	4586 >> Electrical connector assembly	
Code (IGCC)		

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Cable\ Accessories$

