

PRODUCT-DETAILS

755LR-M0260 ELBOW, 600 SERIE DB, 35KV



Extended Product Type	755LR-M0260
Product ID	7TAA122300R0037
EAN	0783786462216
Catalog Description	ELBOW, 600 SERIE DB, 35KV
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Strandec 3/0 /Compacted Solid 4/0 /mmSquared Compact 95

Ordering	
EAN	0783786462216
UPC	783786462216
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	14 in 356 mm
Package Level 1 Height	11.25 in 286 mm

Number of Batteries

Additional Information		
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.	
Brand / Label	Elastimold	
Color	Black	
Current Rating	600 A	
Effective Date	20050518	
Environmental Conditions	Fully Submersible	
Insulation Material	Yes, EPDM Rubber	
Material	Housing - EPDM Rubber	
	2	

Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.370 inch to 1.630 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical	755LR-M0260
Information	
Instructions and	755LR-M0260
Manuals	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Apparatus}\ \to\ \mathsf{Apparatus$

9.25 in

0

235 mm

