

PRODUCT-DETAILS

## 755LR-N0330

## 35KV 600A DB ELBOW WO/TP N0330



General Information		
Extended Product Type	755LR-N0330	
Product ID	7TAA122300R0044	
EAN	0783786406623	
Catalog Description	35KV 600A DB ELBOW WO/TP N0330	
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.515 inch to 1.780 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300.	

Ordering	
EAN	0783786406623
UPC	783786406623
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	14 in 356 mm
Package Level 1 Height	11.25 in 286 mm

Package Level 1 Depth / 9.25 in Length 235 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20030710
Environmental Conditions	Fully Submersible
Includes	Elbow Housing, Compression Lug, Stud, Insulated Plug with Cap, Lubricant, Cable Adapter, Installation Instructions, Crimp Chart
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	755LR-N0330	
Instructions and Manuals	755LR-N0330	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

755LR-N0330 3

