

PRODUCT-DETAILS

755LR-N0360

35KV 600A DB ELBOW WO/TP N0360



General Information		
Extended Product Type	755LR-N0360	
Product ID	7TAA122300R0047	
EAN	0783786659197	
Catalog Description	35KV 600A DB ELBOW WO/TP N0360	
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug a Cable Adapter). Cable Insulation Diameter 1.515 inch to 1.780 inch. Alumine Compression Lug. Conductor Size AWG or kcmil, Compressed Strand	

Ordering	
EAN	078378665919
UPC	783786659197
Country of Origin	United States (US
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece

Additional Information

Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable
	Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	19980108
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	755LR-N0360	
Instructions and Manuals	755LR-N0360	

Classifications		
UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly	

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Cable\ Accessories\ and\ Apparatus\ \rightarrow\ Cable\ Accessories$

