

PRODUCT-DETAILS

755LR-P0410

35KV 600A DB ELBOW WO/TP P0410



General Information	
Extended Product Type	755LR-P0410
Product ID	7TAA122300R0056
EAN	0783786299539
Catalog Description	35KV 600A DB ELBOW WO/TP P0410
Long Description	35kv, 600 Amp, Loadbreak, Elbow, Cable Insulation Diameter 1.725-1.935 inches, Aluminum Lug, Conductor Size 1000 Compressed/Stranded

Ordering	
EAN	0783786299539
UPC	783786299539
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	14 in 356 mm
Package Level 1 Height	11.25 in 286 mm
Package Level 1 Depth / Length	9.25 in 235 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20010829
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.725-1.935 inches
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical	755LR-P0410
Information	
Instructions and	755LR-P0410
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

Categories

755LR-P0410 3

