

PRODUCT-DETAILS

755LR-Q0400 ELBOW,600A DB, 35KV



General Information		
Extended Product Type	755LR-Q0400	
Product ID	7TAA122300R0059	
EAN	0783786477296	
Catalog Description	ELBOW,600A DB, 35KV	
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.900 inch to 2.120 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 900 /Compacted Solid 1000 /mmSquared Compact 500.	

Ordering	
0783786477296	
783786477296	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	14 in 356 mm	
Package Level 1 Height	11.25 in 286 mm	

755LR-Q0400

Package Level 1 Depth / 9.25 in Length 235 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20051108
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.900 inch to 2.120 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Da	ta Sheet, Technical	
Inf	ormation	

Instructions and 755LR-Q0400 Manuals

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

Categories

755LR-Q0400 3

