

PRODUCT-DETAILS

755LR-Q0410

35KV 600A DB ELBOW WO/TP Q0410



General Information		
Extended Product Type	755LR-Q0410	
Product ID	7TAA122300R0060	
EAN	0783786361694	
Catalog Description	35KV 600A DB ELBOW WO/TP Q0410	
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.900 inch to 2.120 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 1000.	

Ordering	
0783786361694	
783786361694	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	3.25 in	
	83 mm	
Package Level 1 Height	8.25 in	
	210 mm	
Package Level 1 Depth /	3.25 in	

Length 83 mm

Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	19990326
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.900 inch to 2.120 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	755LR-Q0410	
Instructions and	755LR-Q0410	
Manuals		

Classifications		
UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly	

Categories

755LR-Q0410 3

