

PRODUCT-DETAILS

## 756LR-K0250

# 35KV 600A DB TP ELBOW ASSEM K0250



General Information		
Extended Product Type	756LR-K0250	
Product ID	7TAA122300R0100	
EAN	0783786353316	
Catalog Description	35KV 600A DB TP ELBOW ASSEM K0250	
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 1.090 inch to 1.310 inch. Conductor Size AWG or kcmil, Compressed Stranded 2/0 /Compacted Solid 3/0 /mmSquared Compact 70.	

Ordering	
0783786353310	
783786353316	
United States (US	
8535908020	
each	

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	14 in 356 mm
Package Level 1 Height	11.25 in 286 mm

Package Level 1 Depth / 9.25 in Length 235 mm

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20020815
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

### **Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	756LR-K0250
Instructions and	756LR-K0250
Manuals	

### Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

### **Categories**

756LR-K0250 3

