

PRODUCT-DETAILS

756LR-L2260 35KV 600A DB TP ELBOW ASSEM L2260



Extended Product Type	756LR-L2260
Product ID	7TAA122300R0124
EAN	0783786024698
Catalog Description	35KV 600A DB TP ELBOW ASSEM L2260
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Copper Compression Lug. Cable Insulation Diameter 1.180 inch to 1.465 inch. Conductor Size AWG or kcmil, Compressed Stranded 3/0 /Compacted Solid 4/0 /mmSquared Compact 95

EAN	0783786024698
UPC	783786024698
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm

Package Level 1 Depth /		
Length		

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20100811
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	756LR-L2260
Instructions and Manuals	756LR-L2260

Classifications		
UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category	4586 >> Electrical connector assembly	
Code (IGCC)		

Categories

Low Voltage Products and Systems \rightarrow Installation Products \rightarrow Cable Accessories and Apparatus \rightarrow Cable Accessories

13.25 in 337 mm

