

PRODUCT-DETAILS

756LR-Q0400-S

35KV 600A DB TP ELBOW ASSEM Q0400S



General Information	
Extended Product Type	756LR-Q0400-S
Product ID	7TAA122300R0159
EAN	5415022105513
Catalog Description	35KV 600A DB TP ELBOW ASSEM Q0400S
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 1.900 inch to 2.120 inch. Conductor Size AWG or kcmil, Compressed Stranded 900 /Compacted Solid 1000 /mmSquared Compact 500. Cold-Shrinkable Jacket Seal Included.

Ordering	
EAN	5415022105513
UPC	783786385430
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	3.25 in 83 mm	
Package Level 1 Height	3.25 in 83 mm	

Package Level 1 Depth / 8.25 in Length 210 mm

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20120301
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold-Shrinkable Jacket Seal.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	756LR-Q0400-S
Instructions and	756LR-Q0400-S
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

756LR-Q0400-S 3

