

PRODUCT-DETAILS

## 756LR-Q0410

## 35KV 600A DB TP ELBOW ASSEM Q0410



General Information		
Extended Product Type	756LR-Q0410	
Product ID	7TAA122300R0160	
EAN	0783786296316	
Catalog Description	35KV 600A DB TP ELBOW ASSEM Q0410	
Long Description	600 Amp, 35KV, DeadBreak, Elbow with Test Point, with Insulated Plug, Cap, Stud, Lug and Cable Adapter, Cable Insulation Diameter 1.900 inch to 2.120 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 1000.	

Ordering	
0783786296316	
783786296316	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	14 in	
	356 mm	
Package Level 1 Height	11.25 in	
	286 mm	
Package Level 1 Depth /	9.25 in	

Length 235 mm

<b>Additional Information</b>	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20010801
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	PRIMARY CABLE ACC. 600 SEP CON
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical Information	756LR-Q0410
Instructions and	756LR-Q0410
Manuals	

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

756LR-Q0410 3

