

PRODUCT-DETAILS

775LR-J2250 35KV 900A DB ELBOW ASSEM J2250



General Information	
Extended Product Type	775LR-J2250
Product ID	7TAA122300R0168
EAN	0783786424658
Catalog Description	35KV 900A DB ELBOW ASSEM J2250
Long Description	900 Amp, 35KV, DeadBreak, Direct Test Elbow with insulated Plug, Cap, Stud, Lug and Cable Adapter, Cable Insulation Diameter 0.980 inch to 1.180 inch. Copper Compression Lug. Conductor Size AWG Compressed Stranded 2/0 /Solid 3/0 /mmSquared 67.43.

Ordering	
EAN	0783786424658
UPC	783786424658
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	14 in 356 mm
Package Level 1 Height	11.25 in 286 mm

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20040318
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical Information	775LR-J2250
Instructions and Manuals	775LR-J2250

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems ightarrow Installation Products ightarrow Cable Accessories and Apparatus ightarrow Cable Accessories

9.25 in 235 mm

