

PRODUCT-DETAILS

775LR-N2440

ELBOW,900A DB, 35KV



General Information	
Extended Product Type	775LR-N2440
Product ID	7TAA122300R0171
EAN	5414363180982
Catalog Description	ELBOW,900A DB, 35KV
Long Description	900 Amp, 35KV, DeadBreak, Direct Test Elbow with insulated Plug, Cap, Stud, Lug and Cable Adapter, Cable Insulation Diameter 1.515 inch to 1.780 inch. Copper Compression Lug. Conductor Size AWG Compressed Stranded 2/0 /Solid 3/0 /mmSquared 67.43.

5414363180982
783786505906
United States (US)
8535908020
each

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	14 in	
	356 mm	
Package Level 1 Height	11.25 in	
	286 mm	
Package Level 1 Depth /	9.25 in	

Length 235 mm

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20061115
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	CILYNDRICAL MULTICONTACT CONNECTOR
Product Type	Deadbreak Elbow Connector
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical	775LR-N2440
Information	
Instructions and	775LR-N2440
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

Categories

775LR-N2440 3

