

PRODUCT-DETAILS

775LR-Q5440-S-CS1634

ELBOW 600A DB, 35KV



General Information	
Extended Product Type	775LR-Q5440-S-CS1634
Product ID	7TAA122300R0174
EAN	5415022058543
Catalog Description	ELBOW 600A DB, 35KV
Long Description	900 Amp, 35kV, 600 Series Elbow with insulated plug, cap, stud, lug and cable adapter. Cable Insulation Diameter 1.900 inch to 2.120 inch. Bi-Metal Compression Lug. Conductor Size kcmil Compressed Stranded 1250. Cold-Shrinkable Jacket Seal Included. Factory lubricated receptacle interface and cable entrance of elbow or bushings extender.

5415022058543
783786068586
United States (US)
8535908020
each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in
	267 mm
Package Level 1 Height	4.38 in
	111 mm

 Package Level 1 Depth /		
Length		

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20110419
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold Shrinkable Jacket Seal
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	775LR-Q5440-S-CS1634	
Instructions and Manuals	775LR-Q5440-S-CS1634	
Classifications		

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly
Code (IGCC)	

Categories

Low Voltage Products and Systems ightarrow Installation Products ightarrow Cable Accessories and Apparatus ightarrow Cable Accessories

13.25 in 337 mm 775LR-Q5440-S-CS1634

