

PRODUCT-DETAILS

776LR-N2320-S 35KV 900A DB TP ELBOW ASSEM N2320S



General Information	
Extended Product Type	776LR-N2320-S
Product ID	7TAA122300R0180
EAN	0783786799572
Catalog Description	35KV 900A DB TP ELBOW ASSEM N2320S
Long Description	900 Amp, 35kV, 600 Series Elbow with Test Point, with Insulated Plug, Cap, Stud, Lug and Cable Adapter. Cold-Shrinkable Jacket Seal Included. Cable Insulation Diameter 1.515 inch to 1.780 inch. Copper Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 450 /Compacted Solid 500/550. Cold-Shrinkable Jacket Seal Included.

Ordering	
EAN	0783786799572
UPC	783786799572
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm

Package Level 1 Depth /	13.25 in
Length	337 mm

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20090108
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold Shrinkable Jacket Seal.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical	776LR-N2320-S
Information	
Instructions and	776LR-N2320-S
Manuals	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Cable}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{C$

