

PRODUCT-DETAILS

## **776LR-P2360-S** ELBOW,900A DB,35KV



General Information	
Extended Product Type	776LR-P2360-S
Product ID	7TAA122300R0184
EAN	0783786799565
Catalog Description	ELBOW,900A DB,35KV
Long Description	900 Amp, 35kV, 600 Series Elbow with Test Point, with Insulated Plug, Cap, Stud, Lug and Cable Adapter. Cold-Shrinkable Jacket Seal Included. Cable Insulation Diameter 1.725 inch to 1.935 inch. Copper Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 650 /Compacted Solid 750 /mmSquared Compact 400. Cold- Shrinkable Jacket Seal Included.

Ordering	
EAN	0783786799565
UPC	783786799565
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm

Package Level 1 Depth / 13.25 in Length 337 mm

Additional Information	
Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20090108
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O- Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold Shrinkable Jacket Seal.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

## **Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	776LR-P2360-S
Instructions and Manuals	776LR-P2360-S

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

## **Categories**

776LR-P2360-S 3

