

PRODUCT-DETAILS

776LR-M5330-S

35KV DB CONNECTOR 600A



General Information

Extended Product Type	776LR-M5330-S
Product ID	7TAA122300R0197
EAN	5415022188134
Catalog Description	35KV DB CONNECTOR 600A
Long Description	900 Amp, 35kV, 600 Series Elbow with Test Point, with Insulated Plug, Cap, Stud, Lug and Cable Adapter. Cold-Shrinkable Jacket Seal Included. Cable Insulation Diameter 1.370 inch to 1.630 inch. Bi-Metal Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300. Cold-Shrinkable Jacket Seal Included.

Ordering

EAN	5415022188134
UPC	075114126274
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

Package Level 1 Depth / Length	1 in 25 mm
--------------------------------	---------------

Additional Information

Application	35 kV, 900 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	900 A
Effective Date	20130910
Environmental Conditions	All Weatheronditions °C
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O-Ring
Special Functions	Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. S - Cold Shrinkable Jacket Seal.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	776LR-M5330-S
Instructions and Manuals	776LR-M5330-S

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

