

PRODUCT-DETAILS

756LR-L2320-SG3

35KV DB 600A T CONNECTOR



General Information

| | |
|-----------------------|--|
| Extended Product Type | 756LR-L2320-SG3 |
| Product ID | 7TAA122300R0203 |
| EAN | 5415022191073 |
| Catalog Description | 35KV DB 600A T CONNECTOR |
| Long Description | 35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Copper Compression Lug. Cable Insulation Diameter 1.180 inch to 1.465 inch. Conductor Size AWG or kcmil, Compressed Stranded 450 /Compacted Solid 500/550. Cold Shrinkable Seal with Copper Braid and Constant Force Spring Included. |

Ordering

| | |
|-------------------------|--------------------|
| EAN | 5415022191073 |
| UPC | 075114131513 |
| Country of Origin | United States (US) |
| Customs Tariff Number | 8535908020 |
| Selling Unit of Measure | each |

Container Information

| | |
|------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 1 in 25 mm |
| Package Level 1 Height | 1 in 25 mm |

| | |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 1 in 25 mm |
|--------------------------------|---------------|

Additional Information

| | |
|--------------------------|---|
| Application | 35 kv, 600 Amp |
| Brand / Label | Elastimold |
| Color | Black |
| Connection Type | Compression |
| Current Rating | 600 A |
| Effective Date | 20130919 |
| Environmental Conditions | Fully Submersible |
| Includes | 1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide |
| Insulation Material | Yes, EPDM Rubber |
| Material | Housing - EPDM Rubber |
| Number of Batteries | 0 |
| Product Name | ELECTRICAL CONNECTOR,>1000V |
| Product Type | Deadbreak Elbow Connector with Test Point |
| Size | Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring. |
| Special Functions | 35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. SG3 Sealing Kit - Cold Shrinkable Seal with Copper Braid and Constant Force Spring. |
| Standards | ANSI/IEEE Standard 386 |
| Temperature Range | -40 to +65 °C |
| Voltage Rating | 35 kV |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 756LR-L2320-SG3 |
| Instructions and Manuals | 756LR-L2320-SG3 |

Classifications

| | |
|------------------------------------|---------------------------------------|
| UNSPSC | 39121421 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

