

PRODUCT-DETAILS

755LR-N2360

35KV DB CONNECTOR 600A N/TEST POINT



General Information		
Extended Product Type	755LR-N2360	
Product ID	7TAA122300R0204	
EAN	5415022194203	
Catalog Description	35KV DB CONNECTOR 600A N/TEST POINT	
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.515 inch to 1.780 inch. Copper Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 650 /Compacted Solid 750 /mmSquared Compact 400.	

5415022194203
075114138017
United States (US)
8535908020
each

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	10.5 in 267 mm	
Package Level 1 Height	4.38 in 111 mm	

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20131010
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators .
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical	755LR-N2360
Information	
Instructions and	755LR-N2360
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

755LR-N2360 3

