

PRODUCT-DETAILS

756LR-J2240-SG335KV DB ELBOW WITH SEALING



General Information	
Extended Product Type	756LR-J2240-SG3
Product ID	7TAA122300R0212
EAN	5415022231472
Catalog Description	35KV DB ELBOW WITH SEALING
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Copper Compression Lug. Cable Insulation Diameter 0.980 inch to 1.180 inch. Conductor Size AWG or kcmil, Compressed Stranded 1/0 /Compacted Solid 2/0. Cold Shrinkable Seal with Copper Braid and Constant Force Spring Included.

Ordering	
5415022231472	
075114164689	
United States (US	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	1 in 25 mm	
Package Level 1 Height	1 in 25 mm	

Package Level 1 Depth / 1 in Length 25 mm

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20140305
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. SG3 Sealing Kit - Cold Shrinkable Seal with Copper Braid and Constant Force Spring.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations	(Document Number)

Data Sheet, Technical	756LR-J2240-SG3
Information	
Instructions and	756LR-J2240-SG3
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

756LR-J2240-SG3 3

