

PRODUCT-DETAILS

## **755LR-G0240-S** 35KV DB ELBOW 600 A W-SEALING



General Information	
Extended Product Type	755LR-G0240-S
Product ID	7TAA122300R0213
EAN	5415022231427
Catalog Description	35KV DB ELBOW 600 A W-SEALING
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 0.760 inch to 0.950 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 1/0 /Compacted Solid 2/0. 200ECS Cold-Shrinkable Jacket Seal Included.

Ordering	
EAN	5415022231427
UPC	075114164634
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20140305
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 0.760 inch to 0.950 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators .
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical	755LR-G0240-S
Information	
Instructions and	755LR-G0240-S
Manuals	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Cable}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{C$ 

1 in 25 mm

