

PRODUCT-DETAILS

## **756LR-K0330-S** 35 KV ELBOW CONNECTOR 600A



| General Information   |   |
|-----------------------|---|
| Extended Product Type | 756LR-K0330-S   |
| Product ID            | 7TAA122300R0231   |
| EAN                   | 0075114179874   |
| Catalog Description   | 35 KV ELBOW CONNECTOR 600A  |
| Long Description      | 35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug<br>and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 1.090 inch<br>to 1.310 inch. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted<br>Solid 600 /mmSquared Compact 250/300. Cold-Shrinkable Jacket Seal Included. |

| Ordering                |                    |
|-------------------------|--------------------|
| EAN                     | 0075114179874      |
| UPC                     | 075114179874       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

| Container Information  |                   |
|------------------------|-------------------|
| Package Level 1 Units  | 1 piece           |
| Package Level 1 Width  | 10.5 in<br>267 mm |
| Package Level 1 Height | 4.38 in<br>111 mm |

| Package Level 1 Depth / |  |  |
|-------------------------|--|--|
| Length                  |  |  |
|                         |  |  |

| Additional Information      |  |
|-----------------------------|--|
| Application                 | 35 kv, 600 Amp   |
| Brand / Label               | Elastimold   |
| Color                       | Black  |
| Connection Type             | Compression  |
| Current Rating              | 600 A  |
| Effective Date              | 20140623   |
| Environmental<br>Conditions | Fully Submersible  |
| Includes                    | 1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3<br>Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction<br>Sheets, V.D. Cap-Peroxide   |
| Insulation Material         | Yes, EPDM Rubber   |
| Material                    | Housing - EPDM Rubber  |
| Number of Batteries         | 0  |
| Product Name                | ELECTRICAL CONNECTOR,>1000V  |
| Product Type                | Deadbreak Elbow Connector with Test Point  |
| Size                        | Width 12.28 inches, 13.93 inches from Bottom Edge to Center of<br>Installation O-Ring.   |
| Special Functions           | 35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded<br>rubber housing. 100 percent peroxide-cured construction includes<br>insulation and conductive EPDM materials. Can be easily connected or<br>disconnected using standard hand tools and equipment in a de-energized<br>state. S - Cold-Shrinkable Jacket Seal. |
| Standards                   | ANSI/IEEE Standard 386   |
| Temperature Range           | -40 to +65 °C  |
| Voltage Rating              | 35 kV  |

| Data Sheet, Technical | 756LR-K0330-S |
|-----------------------|---------------|
| Information           |               |
| Instructions and      | 756LR-K0330-S |
| Manuals               |               |

| Classifications                       |                                       |  |
|---------------------------------------|---------------------------------------|--|
| UNSPSC                                | 39121421                              |  |
| WEEE Category                         | Product Not in WEEE Scope             |  |
| IDEA Granular Category<br>Code (IGCC) | 4586 >> Electrical connector assembly |  |

## Categories

Low Voltage Products and Systems  $\rightarrow$  Installation Products  $\rightarrow$  Cable Accessories and Apparatus  $\rightarrow$  Cable Accessories

13.25 in 337 mm

