

PRODUCT-DETAILS

755LR-N2320 35KV 600A DB ELBOW WO/TP N2320



Extended Product Type	755LR-N2320
Product ID	7TAA122300R0241
EAN	0075114197656
Catalog Description	35KV 600A DB ELBOW WO/TP N2320
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.515 inch to 1.780 inch. Copper Compression Lug. Conductor Size AWG or kcmil, Compressed Strandec 450 /Compacted Solid 500/550

Ordering	
EAN	0075114197656
UPC	075114197656
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	13.25 in 337 mm
Package Level 1 Height	4.38 in 111 mm

Application

Brand / Label

Current Rating

Color

Additional Information

Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Elastimold
Black
600 A

Effective Date	20140923
Environmental	Fully Submersible
Conditions	
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Chast Tashairal	7551 D N0000
Data Sheet, Technical	755LR-N2320
Information	
Instructions and	755LR-N2320
Manuals	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Apparatus}\ \to\ \mathsf{Apparatus$

10.5 in

267 mm

