

PRODUCT-DETAILS

# 776LR-K2260

## 35KV DB ELBOW 900A NO SEALING KIT



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | 776LR-K2260                                  |
| Product ID            | 7TAA122300R0247                              |
| EAN                   | 0075114239042                                |
| Catalog Description   | 35KV DB ELBOW 900A NO SEALING KIT            |
| Long Description      | 35kv Dead Break Elbow 900 Amp No Sealing Kit |

### Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0075114239042      |
| UPC                     | 075114239042       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

### Container Information

|                                |                    |
|--------------------------------|--------------------|
| Package Level 1 Units          | 1 piece            |
| Package Level 1 Width          | 10.5 in<br>267 mm  |
| Package Level 1 Height         | 4.38 in<br>111 mm  |
| Package Level 1 Depth / Length | 13.25 in<br>337 mm |

---

## Additional Information

|                          |  |
|--------------------------|--|
| Application              | 35 kV, 900 Amps  |
| Brand / Label            | Elastimold   |
| Color                    | Black  |
| Connection Type          | Compression  |
| Current Rating           | 900 A  |
| Effective Date           | 20150423   |
| Environmental Conditions | All Weatheronditions °C  |
| Includes                 | 1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide   |
| Insulation Material      | Yes, EPDM Rubber   |
| Material                 | Housing - EPDM Rubber  |
| Number of Batteries      | 0  |
| Product Name             | ELECTRICAL CONNECTOR,>1000V  |
| Product Type             | Deadbreak Elbow Connector with Test Point  |
| Size                     | 12.28 inch Wide, 13.93 inch from bottom edge to Center of Installation O-Ring  |
| Special Functions        | Fully Shielded, Fully Submersible Molded Rubber Housing. 100 percent Peroxide-Cured Construction includes Insulation and Conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. |
| Standards                | ANSI/IEEE Standard 386   |
| Temperature Range        | -40 to +65 °C  |
| Voltage Rating           | 35 kV  |

---

## Certificates and Declarations (Document Number)

|                                   |             |
|-----------------------------------|-------------|
| Data Sheet, Technical Information | 776LR-K2260 |
| Instructions and Manuals          | 776LR-K2260 |

---

## Classifications

|                                    |                                       |
|------------------------------------|---------------------------------------|
| UNSPSC                             | 39121421                              |
| WEEE Category                      | Product Not in WEEE Scope             |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

---

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

