

PRODUCT-DETAILS

# 755LR-K0250-SG3

## 35KV 600A DB ELBOW WO/TP K0250 SG3



### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | 755LR-K0250-SG3   |
| Product ID            | 7TAA122300R0266   |
| EAN                   | 0075114312134   |
| Catalog Description   | 35KV 600A DB ELBOW WO/TP K0250 SG3  |
| Long Description      | 35kv, 600 Amp, Loadbreak, Elbow, with Sealing Kit, Cable Insulation Diameter 1.090-1.310 inches, Aluminum Lug, Conductor Size 2/0 Compressed/Stranded or 3/0 Compact/Solid. |

### Ordering

|                         |                    |
|-------------------------|--------------------|
| EAN                     | 0075114312134      |
| UPC                     | 075114312134       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

### Container Information

|                         |               |
|-------------------------|---------------|
| Package Level 1 Units   | 1 piece       |
| Package Level 1 Width   | 1 in<br>25 mm |
| Package Level 1 Height  | 1 in<br>25 mm |
| Package Level 1 Depth / | 1 in          |

Length 25 mm

## Additional Information

|                          |   |
|--------------------------|---|
| Application              | Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.   |
| Brand / Label            | Elastimold  |
| Color                    | Black   |
| Current Rating           | 600 A   |
| Effective Date           | 20160724  |
| Environmental Conditions | Fully Submersible   |
| Insulation Material      | Yes, EPDM Rubber  |
| Material                 | Housing - EPDM Rubber   |
| Number of Batteries      | 0   |
| Product Name             | ELECTRICAL CONNECTOR,>1000V   |
| Product Type             | Deadbreak Elbow Connector   |
| Size                     | Cable Insulation Diameter 1.090-1.310 inches  |
| Special Functions        | 100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators . |
| Standards                | ANSI/IEEE Standard 386  |
| Temperature Range        | -40 to +65 °C   |
| Voltage Rating           | 35 kV   |

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 755LR-K0250-SG3 |
| Instructions and Manuals          | 755LR-K0250-SG3 |

## Classifications

|                                    |                                       |
|------------------------------------|---------------------------------------|
| UNSPSC                             | 39121421                              |
| WEEE Category                      | Product Not in WEEE Scope             |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

