

PRODUCT-DETAILS

755LR-M0320-SG3

35KV 600A DB ELBOW WO/TP M0320 SG3



General Information	
Extended Product Type	755LR-M0320-SG3
Product ID	7TAA122300R0268
EAN	0075114314008
Catalog Description	35KV 600A DB ELBOW WO/TP M0320 SG3
Long Description	35kv, 600 Amp, Loadbreak, Elbow, with Sealing Kit, Cable Insulation Diameter 1.370- 1.630 inches, Aluminum Lug, Conductor Size 500 Compact/Solid.

Ordering	
EAN	0075114314008
UPC	075114314008
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm
Package Level 1 Depth / Length	13.25 in 337 mm

Additional Information	
Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20160727
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.370-1.630 inches,
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755LR-M0320-SG3
Instructions and	755LR-M0320-SG3
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

Categories

755LR-M0320-SG3 3

