

PRODUCT-DETAILS

756LR-N0410

35KV 600A ELBOW NO SEALING KIT



General Information		
Extended Product Type	756LR-N0410	
Product ID	7TAA122300R0274	
EAN	0075114330480	
Catalog Description	35KV 600A ELBOW NO SEALING KIT	
Long Description	35kV, 600 Amps, Deadbreak Elbow with Test Point. Cable Insulation Diameter Range 1.515 to 1.780 inch, Aluminum Lug, Conductor Size 1000 Stranded/Compressed. No Sealing Kit.	

Ordering	
0075114330480	
075114330480	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	10.5 in 267 mm	
Package Level 1 Height	4.38 in	
	111 mm	
Package Level 1 Depth /	13.25 in	

Length 337 mm

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20170207
Environmental Conditions	Fully Submersible
Includes	1 Elbow Connector Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 1 Cable Adapter, 1 Tube Lubricant, 1 Crimp Chart, 1 V.D. Cap- Peroxide, Installation Instruction Sheets
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical Information	756LR-N0410
Instructions and	756LR-N0410
Manuals	

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

756LR-N0410 3

