

PRODUCT-DETAILS

## 756LR-R0440

## 35KV 600A ELBOW NO-SEALING KIT



General Information		
Extended Product Type	756LR-R0440	
Product ID	7TAA122300R0287	
EAN	0075114359580	
Catalog Description	35KV 600A ELBOW NO-SEALING KIT	
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 2.115 inch to 2.235 inch. Conductor Size kcmil Compressed Stranded 1250 kcmil.	

Ordering	
0075114359580	
075114359580	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	10.5 in	
	267 mm	
Package Level 1 Height	4.38 in	
	111 mm	
Package Level 1 Depth /	13.25 in	

Length 337 mm

<b>Additional Information</b>	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20180108
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical Information	756LR-R0440
Instructions and	756LR-R0440
Manuals	

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4586 >> Electrical connector assembly

## Categories

756LR-R0440 3

