

PRODUCT-DETAILS

# 755LR-N5330

## 35KV 600A ELBOW NO-SEALING KIT



### General Information

Extended Product Type	755LR-N5330
Product ID	7TAA122300R0291
EAN	0075114378499
Catalog Description	35KV 600A ELBOW NO-SEALING KIT
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.515 inch to 1.780 inch. Bi-Metal Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300.

### Ordering

EAN	0075114378499
UPC	075114378499
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm

Package Level 1 Depth / Length	13.25 in 337 mm
--------------------------------	--------------------

## Additional Information

Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20180817
Environmental Conditions	Fully Submersible
Includes	Elbow Housing, Compression Lug, Stud, Insulated Plug with Cap, Lubricant, Cable Adapter, Installation Instructions, Crimp Chart
Insulation Material	Yes EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR>1000V
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators . Bi-Metal Lug.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

## Classifications

UNSPSC	39121421
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

