

PRODUCT-DETAILS

## **756LR-PAC04-S**

# 35KV 600A DB TP ELBOW ASSEM PACO4S



General Information		
Extended Product Type	756LR-PAC04-S	
Product ID	7TAA122300R0299	
EAN	0075114391214	
Catalog Description	35KV 600A DB TP ELBOW ASSEM PAC04S	
Long Description	35kV, 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Shearbolt Lug and Cable Adapter). Tin-Plated Aluminum Shearbolt Lug. Cable Insulation Diameter 1.725 inch to 1.935 inch. Conductor Size Range for Compressed / Stranded / Compacted / Solid 750 to 1250 kcmil. Cold-Shrinkable Jacket Seal Included.	

Ordering	
EAN	0075114391214
UPC	075114391214
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm

Package Level 1 Depth / 13.25 in Length 337 mm

Additional Information	
Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Shear Bolt
Current Rating	600 A
Effective Date	20181211
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Shearbolt Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets
Insulation Material	Yes EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring
Special Functions	35kV, 600 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

## Certificates and Declarations (Document Number)

Data Sheet, Technical	756LR-PAC04-S
Information	
Instructions and	756LR-PAC04-S
Manuals	

### Classifications

UNSPSC	39121421
IDEA Granular Category	4586 >> Electrical connector assembly
Code (IGCC)	

### Categories

756LR-PAC04-S 3

