

PRODUCT-DETAILS

## **756LR-J0300** 35KV 600A DB ELBOW NO-SEALING KIT



| Extended Product Type | 756LR-J0300   |
|-----------------------|---|
| Product ID            | 7TAA122300R0302   |
| EAN                   | 0075114401609   |
| Catalog Description   | 35KV 600A DB ELBOW NO-SEALING KIT   |
| Long Description      | 35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug<br>and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 0.980 inch<br>to 1.180 inch. Conductor Size Compressed Stranded 350 kcmil or Compacted Solid 400<br>kcmil or mmSquared Compact 185. |

| Ordering                |                    |
|-------------------------|--------------------|
| EAN                     | 0075114401609      |
| UPC                     | 075114401609       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8535908020         |
| Selling Unit of Measure | each               |

| Container Information  |               |  |
|------------------------|---------------|--|
| Package Level 1 Units  | 1 piece       |  |
| Package Level 1 Width  | 1 in<br>25 mm |  |
| Package Level 1 Height | 1 in<br>25 mm |  |

| Additional Information      |   |
|-----------------------------|---|
| Application                 | 35 kv, 600 Amp  |
| Brand / Label               | Elastimold  |
| Color                       | Black   |
| Connection Type             | Compression   |
| Current Rating              | 600 A   |
| Effective Date              | 20190621  |
| Environmental<br>Conditions | Fully Submersible   |
| Includes                    | 1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3<br>Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction<br>Sheets, V.D. Cap-Peroxide  |
| Insulation Material         | Yes EPDM Rubber   |
| Material                    | Housing - EPDM Rubber   |
| Number of Batteries         | 0   |
| Product Name                | ELECTRICAL CONNECTOR>1000V  |
| Product Type                | Deadbreak Elbow Connector with Test Point   |
| Size                        | Width 12.28 inches, 13.93 inches from Bottom Edge to Center of<br>Installation O-Ring.  |
| Special Functions           | 35kV, 600 Amp Deadbreak Elbow. Fully shielded, fully submersible molded<br>rubber housing. 100 percent peroxide-cured construction includes<br>insulation and conductive EPDM materials. Can be easily connected or<br>disconnected using standard hand tools and equipment in a de-energized<br>state. |
| Standards                   | ANSI/IEEE Standard 386  |
| Temperature Range           | -40 to +65 °C   |
| Voltage Rating              | 35 kV   |

| Data Sheet, Technical | 756LR-J0300 |
|-----------------------|-------------|
| Information           |             |
| Instructions and      | 756LR-J0300 |
| Manuals               |             |

| Classifications                       |                                       |  |
|---------------------------------------|---------------------------------------|--|
| UNSPSC                                | 39121421                              |  |
| IDEA Granular Category<br>Code (IGCC) | 4586 >> Electrical connector assembly |  |

## Categories

Low Voltage Products and Systems  $\rightarrow$  Installation Products  $\rightarrow$  Cable Accessories and Apparatus  $\rightarrow$  Cable Accessories

1 in 25 mm

