

PRODUCT-DETAILS

756LR-G0250-SG3

35KV 600A DB ELBOW W-SEALING KIT



General Information

Extended Product Type	756LR-G0250-SG3
Product ID	7TAA122300R0304
EAN	0075114407175
Catalog Description	35KV 600A DB ELBOW W-SEALING KIT
Long Description	35kV 600 Series Deadbreak Elbow with Test Point (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Aluminum Compression Lug. Cable Insulation Diameter 0.760 inch to 0.950 inch. Conductor Size AWG or kcmil, Compressed Stranded 2/0 or Compacted Solid 3/0. Cold Shrinkable Seal with Copper Braid and Constant Force Spring. Width 12.28 inch, Length 13.93 inch from bottom edge to Center of Bushing. Diameter 3.83 inch.

Ordering

EAN	0075114407175
UPC	075114407175
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	9 in 229 mm
Package Level 1 Height	11 in

	279 mm
Package Level 1 Depth / Length	14 in
	356 mm

Additional Information

Application	35 kv, 600 Amp
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20200131
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Main Type	ELASTIMOLD 600A SEPARABLE CONNECTORS
Product Name	ELECTRICAL CONNECTOR>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inch, Length 13.93 inch from bottom edge to Center of Bushing. Diameter 3.83 inch.
Special Functions	35kV, 600 Amp Deadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	756LR-G0250-SG3
Instructions and Manuals	756LR-G0250-SG3

Classifications

UNSPSC	39121421
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

