

PRODUCT-DETAILS

750-J2

35KV 600A DEADBRK 2PT JUNCTION



General Information

Extended Product Type	750-J2
Product ID	7TAA122320R0000
EAN	0783786630103
Catalog Description	35KV 600A DEADBRK 2PT JUNCTION
Long Description	35kV 600 Series Deadbreak 2-Point Junction, includes Rubber Junction, Stainless Steel U-Straps and Back Plate

Ordering

EAN	0783786630103
UPC	783786630103
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
-----------------------	---------

Additional Information

Application	Designed for subsurface, vault or padmount applications and can be used for sectionalizing, looping, tapping, and equipment bypass.
-------------	---

Brand / Label	Elastimold
Effective Date	19980108
Material	Stainless Steel Mounting Bracket, EPDM Rubber Junction.
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Junction
Size	6.85 inches (173.6 mm) Tall, 6.75 inch (171.5 mm) Wide, 19.00 inch (482.6 mm) Long, 4.00 inch (101.6 mm) Center Junction to Center Junction. 5.50 inch (139.7 mm) Center Slot to Center Slot on Short Side, 8.00 inch (203.2 mm) on Long Side, and 1.50 inch (38.1 mm) Center Slot from Edge on Long Side.
Special Functions	35kV, 600 Amp Deadbreak 2-Way Junction. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provides mating for Elastimold Elbow connectors. Stainless Steel Mounting Bracket.
Standards	ANSI/IEEE Standard 386

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	750-J2
Instructions and Manuals	750-J2

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

