

PRODUCT-DETAILS

750SOP

35KV 600 AMP STAND-OFF PLUG



General Information

Extended Product Type	750SOP
Product ID	7TAA122340R0000
EAN	0783786628803
Catalog Description	35KV 600 AMP STAND-OFF PLUG
Long Description	35 kV, 600 Series Deadbreak Insulated Parking Bushing, Stand-Off Plug. Length 5.062 inch, Widest Diameter 3 inch. Epoxy.

Ordering

EAN	0783786628803
UPC	783786628803
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	5.5 in 140 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	8.5 in 216 mm

Additional Information

Application	The 750SOP is inserted into the parking stand with an insulated hot stick and secured in place. Mating Elastimold 755LR/756LR deadbreak elbows can then be placed on the 750SOP to provide a fully shielded and fully submersible connection. Provisions for grounding the 750SOP mounting bracket are included.
Brand / Label	Elastimold
Effective Date	19980115
Material	EPDM Rubber
Number of Batteries	0
Product Name	"ELECTRICAL CONNECTOR,>1000V"
Product Type	Parking Bushing
Size	3.00 inch (76.2 mm) Diameter, 5.00 inch (127.0 mm) Length, 5.02 inch (127.6 mm) Center of Bushing to top of Eye Bolt.
Special Functions	Fully rated 35kV, 600 Amp Deadbreak Insulated Parking Bushing. Allows visible external separation, isolation, and dead-ending. Stainless Steel Bracket. Hot Stick Operable.
Standards	ANSI/IEEE Standard 386

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	750SOP
Instructions and Manuals	750SOP

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

