

PRODUCT-DETAILS

755DLR-J0240

35KV DB ELBOW HOUSING



General Information

Extended Product Type	755DLR-J0240
Product ID	7TAA122350R0005
EAN	0075114213219
Catalog Description	35KV DB ELBOW HOUSING
Long Description	600 Amp, 35KV, Direct Test Elbow, with Insulated Plug, Cap, Stud, Lug and Cable Adapter, Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor Size AWG Compressed Stranded 1/0 or Compacted/Solid 2/0.

Ordering

EAN	0075114213219
UPC	075114213219
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	10.5 in 267 mm
Package Level 1 Height	4.38 in 111 mm
Package Level 1 Depth /	13.25 in

Length	337 mm
--------	--------

Additional Information

Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20150107
Environmental Conditions	All Weatheronditions °C
Includes	Elbow Connector Housing, Compression Lug, Stud, Insulated Plug with Cap, Cable Adapter, Lubricant, Installation Instructions, Crimp Chart
Insulation Material	Yes, EPDM Rubber
Material	Aluminum Lug, EPDM Rubber Body
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Direct Test Elbow Connector
Size	T-Body 12.23 inch wide. 14.30 inch from bottom of T-Body to center of Bushing Interface entrance.
Special Functions	Fully Shielded, Fully Submersible. Comes with Insulated Plug, Cap, Stud, Lug and Cable Adapter
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755DLR-J0240
Instructions and Manuals	755DLR-J0240

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

