

PRODUCT-DETAILS

755L2-J0230

L-KIT,2 WAY,600A DB, 35KV



General Information

Extended Product Type	755L2-J0230
Product ID	7TAA122370R0004
EAN	5414363180043
Catalog Description	L-KIT,2 WAY,600A DB, 35KV
Long Description	600 Amp, 35kV, 600 Series Deadbreak 2-Way L-Kit. Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded #1/ Compacted Solid 1/0 /mmSquared Compact 50.

Ordering

EAN	5414363180043
UPC	783786504909
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth /	1 in

Length 25 mm

Additional Information

Application	Used to connect two cable ends and using the two insulating plugs as test points allows for capacitive voltage testing
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20061018
Environmental Conditions	Fully Submersible
Includes	(2) Elbows, (2) Cable Size Adapters, (2) Compression Lugs, (6) Tubes of Lubricant, (2) Basic Insulating Plugs with Caps, (2) Studs, (1) Connecting Plug, Installation Instructions, Crimp Chart.
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak 2-Way L Kit
Size	25.38 inch Wide, 13.93 inch from Bottom of T to Center of Plug.
Special Functions	No Seal
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755L2-J0230
Instructions and Manuals	755L2-J0230

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

