

PRODUCT-DETAILS

755L2-J2250-SG3 35KV 600A L2 SPLICE W-SEALING



Extended Product Type	755L2-J2250-SG
Product ID	7TAA122370R001
EAN	007511423945
Catalog Description	35KV 600A L2 SPLICE W-SEALING
Long Description	600 Amp, 35kV, 600 Series Deadbreak 2-Way L-Kit. Cable Insulation Diameter 0.980 inch to 1.180 inch. Aluminum Compression Lug. Conductor Size AWG, Compressed Stranded 2/0 or Compacted Solid 3/0. With Cold-Shrinkable Seal with Copper Braic and Constant Force Spring

Ordering	
EAN	0075114239455
UPC	075114239455
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

	1 in
25	mm

Additional Information	
Application	Used to connect two cable ends and using the two insulating plugs as test points allows for capacitive voltage testing
Brand / Label	Elastimolo
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20150423
Environmental Conditions	Fully Submersible
Includes	(2) Elbows, (2) Cable Size Adapters, (2) Compression Lugs, (6) Tubes of Lubricant, (2) Basic Insulating Plugs with Caps, (2) Studs, (1) Connecting Plug, Installation Instructions, Crimp Chart.
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak 2-Way L Kit
Size	25.38 inch Wide, 13.93 inch from Bottom of T to Center of Plug.
Special Functions	Cold-Shrinkable Seal with Copper Braid and Constant Force Spring
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Data Sheet, Technical	755L2-J2250-SG3
Information	12215-3520-363
Instructions and	755L2-J2250-SG3
Manuals	

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems ightarrow Installation Products ightarrow Cable Accessories and Apparatus ightarrow Cable Accessories

