

PRODUCT-DETAILS

755LRTP-M0330-DRG

35kv 600/200A S-OP LB W/TP M0330DRG



General Information

| | |
|-----------------------|---|
| Extended Product Type | 755LRTP-M0330-DRG |
| Product ID | 7TAA122400R0089 |
| EAN | 0783786021215 |
| Catalog Description | 35kv 600/200A S-OP LB W/TP M0330DRG |
| Long Description | 600 Amp, 35kV, Stick-Op Connector Kit with Test Point, Insulated Cap and Reducing Tap Plug. Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300. |

Ordering

| | |
|-------------------------|--------------------|
| EAN | 0783786021215 |
| UPC | 783786021215 |
| Country of Origin | United States (US) |
| Customs Tariff Number | 8535908020 |
| Selling Unit of Measure | each |

Container Information

| | |
|------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 1 in 25 mm |
| Package Level 1 Height | 1 in 25 mm |

| | |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 1 in 25 mm |
|--------------------------------|---------------|

Additional Information

| | |
|--------------------------|--|
| Application | Mates with a 600 Amp elbow interface and provides a 200 Amp load break tap, an access hole thru the bore of the reducing tap plug allows use of a 600AT operating tool to bolt and secure the component to a mating 600 Amp elbow and apparatus bushing. |
| Brand / Label | Elastimold |
| Color | Black |
| Current Rating | 600 to 200 A |
| Effective Date | 20100721 |
| Environmental Conditions | Fully Submersible |
| Includes | Elbow Housing, Reducing Tap Plug, Insulated Cap, Cable Size Adapter, Compression Lug, Lubricant, Instruction Sheet, Crimp Chart. |
| Insulation Material | Yes, EPDM Rubber |
| Material | Housing - EPDM Rubber |
| Number of Batteries | 0 |
| Product Name | ELECTRICAL CONNECTOR,>1000V |
| Product Type | Stick-OP Elbow Connector |
| Size | Cable Insulation Diameter 1.370 inch to 1.630 inch. |
| Special Functions | Test Point. 35kV Reducing Tap Plug. Includes Hex-Broach for Torque Installation. Peroxide-Cured Insulation and Jacket. |
| Standards | ANSI/IEEE Standard 386 |
| Temperature Range | -40 to +65 °C |
| Voltage Rating | 35 kV |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-------------------|
| Data Sheet, Technical Information | 755LRTP-M0330-DRG |
| Instructions and Manuals | 755LRTP-M0330-DRG |

Classifications

| | |
|------------------------------------|---------------------------------------|
| UNSPSC | 39121421 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 4586 >> Electrical connector assembly |

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

