

PRODUCT-DETAILS

756LRTP-K0270-DRG

35KV 600A DB S-OP CONN TP K0270-DRG



General Information

Extended Product Type	756LRTP-K0270-DRG
Product ID	7TAA122400R0094
EAN	0783786861682
Catalog Description	35KV 600A DB S-OP CONN TP K0270-DRG
Long Description	600 Amp, 35kV, Deadbreak, Stick-Op Connector Kit, with Capacitive test point, Aluminum Compression Lug. Cable Insulation Diameter 1.090 inch to 1.310 inch. Conductor Size AWG or kcmil, Compressed Stranded 4/0 /Compacted Solid 250 /mmSquared Compact 125. With Insulated Cap.

Ordering

EAN	0783786861682
UPC	783786861682
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	13.25 in 337 mm
Package Level 1 Height	10.5 in 267 mm

Package Level 1 Depth / Length	4.37 in 111 mm
--------------------------------	-------------------

Additional Information

Application	Connect 600 Amp interface to 200 Amp Loadbreak Tap
Brand / Label	Elastimold
Color	Black
Current Rating	600 to 200 A
Effective Date	20091118
Enclosure Type	Yes, EPDM Rubber
Environmental Conditions	All Weatheronditions °C
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Stick Op Reducing Tap Plug Connector with Test Point
Special Functions	Reducing Tap Plug 600 to 200 Amps. Test Point. Provides an External Visible Break by Hotstick Removal of the Elbow.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	756LRTP-K0270-DRG
Instructions and Manuals	756LRTP-K0270-DRG

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

