

PRODUCT-DETAILS

756LRTP-P0360

35KV 600A DB S-OP CONN TP P0360



General Information

Extended Product Type	756LRTP-P0360
Product ID	7TAA122400R0096
EAN	0783786463190
Catalog Description	35KV 600A DB S-OP CONN TP P0360
Long Description	600 Amp, 35kV, Deadbreak, Stick-Op Connector Kit, with Capacitive test point, Aluminum Compression Lug. Cable Insulation Diameter 1.725 inch to 1.935 inch. Conductor Size AWG or kcmil, Compressed Stranded 650 /Compacted Solid 750 /mmSquared Compact 400.

Ordering

EAN	0783786463190
UPC	783786463190
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

Package Level 1 Depth /
Length

1 in
25 mm

Additional Information

Application	Connect 600 Amp interface to 200 Amp Loadbreak Tap
Brand / Label	Elastimold
Color	Black
Current Rating	600 to 200 A
Effective Date	20050518
Enclosure Type	Yes, EPDM Rubber
Environmental Conditions	All Weatheronditions °C
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Stick Op Reducing Tap Plug Connector with Test Point
Special Functions	Reducing Tap Plug 600 to 200 Amps. Test Point. Provides an External Visible Break by Hotstick Removal of the Elbow.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	756LRTP-P0360
Instructions and Manuals	756LRTP-P0360

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

