

PRODUCT-DETAILS

756LR-M0330-SG3 35KV 600A DB ELBOW M0330 SG3



General Information	
Extended Product Type	756LR-M0330-SG3
Product ID	7TAA122400R0166
EAN	0075114322973
Catalog Description	35KV 600A DB ELBOW M0330 SG3
Long Description	15/25/35kV, 600 Amp, Deadbreak Elbow, with Test Point (includes Plug, Cap, Stud, Lug and Cable Adapter), Cable Insulation Diameter 1.370-1.630 inches, Aluminum Lug, Conductor Size 500 kcmils Stranded Compressed, With SG3 Sealing Kit - Cold Shrinkable Seal with Copper Braid and Contant Force Spring.

Ordering	
0075114322973	
075114322973	
United States (US)	
8535908020	
each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	1 in 25 mm	
Package Level 1 Height	1 in 25 mm	

Package Level 1 Depth / 1 in Length 25 mm

Additional Information	
Application	15/25/35kV, 600 Amps
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20161028
Environmental Conditions	Fully Submersible
Includes	1 Elbow Housing, 1 Compression Lug, 1 Stud, 1 Insulated Plug with Cap, 3 Tubes Lubricant, 1 Cable adapter, 1 Crimp Chart, Installation Instruction Sheets, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Deadbreak Elbow Connector with Test Point
Size	Width 12.28 inches, 13.93 inches from Bottom Edge to Center of Installation O-Ring.
Special Functions	SG3 Sealing Kit - Cold Shrinkable Seal with Copper Braid and Constant Force Spring.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	756LR-M0330-SG3	
Instructions and Manuals	756LR-M0330-SG3	

Classifications		
UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly	

Categories

756LR-M0330-SG3 3

