

PRODUCT-DETAILS

# 755ETP-M0300-DRG

## 35KV 600A ETP ELBOW KIT M0300-DRG



### General Information

Extended Product Type	755ETP-M0300-DRG
Product ID	7TAA122410R0085
EAN	0783786461097
Catalog Description	35KV 600A ETP ELBOW KIT M0300-DRG
Long Description	600 Amp, 35kV, Deadbreak, Test and Ground Connector kit, includes Insulated cap, reducing tap plug, elbow housing, cable adapter and 0370 style compression lug. 600ATM assembly tool required, 50-60 foot/pounds torque wrench required but not included. Aluminum Compression Lug. Cable Insulation Diameter 1.370 inch to 1.630 inch. Conductor Size AWG or kcmil, Compressed Stranded 350 /Compacted Solid 400 /mmSquared Compact 185.

### Ordering

EAN	0783786461097
UPC	783786461097
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in

	25 mm
Package Level 1 Depth / Length	1 in
	25 mm

## Additional Information

Application	600 Amps, 35kV
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20050510
Insulation Material	EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Window-Op Connector
Size	Cable Insulation Diameter 1.370 inch to 1.630 inch.
Special Functions	Includes Insulated Cap
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755ETP-M0300-DRG
Instructions and Manuals	755ETP-M0300-DRG

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

