

PRODUCT-DETAILS

756ETP-N0330-S

600 SERIES ELBOW W/TEST POINT



General Information

Extended Product Type	756ETP-N0330-S
Product ID	7TAA122410R0095
EAN	5415022072860
Catalog Description	600 SERIES ELBOW W/TEST POINT
Long Description	600 Amp, 35kV, Deadbreak, Elbow Tap Plug, Aluminum Compression Lug. Cable Insulation Diameter 1.515 inch to 1.780 inch. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300. Cold-Shrinkable Jacket Seal Included.

Ordering

EAN	5415022072860
UPC	783786083305
Country of Origin	United States (US)
Customs Tariff Number	8535908020
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

Package Level 1 Depth /
Length

1 in
25 mm

Additional Information

Application	600 Amps, 35kV
Brand / Label	Elastimold
Color	Black
Connection Type	Compression
Current Rating	600 A
Effective Date	20110720
Insulation Material	EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Window-Op Connector
Size	Cable Insulation Diameter 1.515 inch to 1.780 inch.
Special Functions	Includes Sealing Kit
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	756ETP-N0330-S
Instructions and Manuals	756ETP-N0330-S

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

