

PRODUCT-DETAILS

750LB

INSULATING PLUG, 600A, 35KV



General Information

Extended Product Type	750LB
Product ID	7TAA122590R0010
EAN	5414363176633
Catalog Description	INSULATING PLUG, 600A, 35KV
Long Description	35kV 600 Series Deadbreak Insulating Plug / Stand-Off Plug. Overall Length 5 inch, Widest Diameter 3 inch. Epoxy Housing.

Ordering

EAN	5414363176633
UPC	783786488612
Country of Origin	United States (US)
Customs Tariff Number	8546900000
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm

Additional Information

Application	Designed to provide a threaded mountable plug for use in cam-op cable joint kits. The 750LB is threaded onto the hardware aligning bracket and the retaining sleeves are threaded into bushing.
Brand / Label	Elastimold
Effective Date	20060322
Material	EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL INSULATOR
Product Type	Insulating Plug
Size	3.00 inch (76.2 mm) Diameter, 5.00 inch (127.0 mm) Length.
Special Functions	Fully rated 35kV, 600 Amp Deadbreak Insulated Plug. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and circuit protection.
Standards	ANSI/IEEE Standard 386

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	750LB
Instructions and Manuals	750LB

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

