

PRODUCT-DETAILS

ABW 8350-1 SLCQDISC TRANS CONN 12-350 1 80 SLO OI



General Information		
Extended Product Type	ABW 8350-1 SLC	
Product ID	7TAA261300R0121	
EAN	0783786689941	
Catalog Description	QDISC TRANS CONN 12-350 1 80 SLO OI	
Long Description	Aluminum Quick Disconnect Transformer Connectors - ABW In-line bar, Cable range #12 to 350 kcmil, length 10-9/16 inches, Stud size 1 inch, outlets 8, with Street Light Outlet Option, includes Oxide Inhibitor and Tin Plated Screws. Dual Rated to Accept Aluminum or Copper Conductors. ANSI C119.4 Specifications.	

Ordering	
0783786689941	
783786689941	
United States (US)	
8536904000	
each	

Container Information		
Package Level 1 Units	20 piece	
Package Level 1 Width	1 in 25 mm	
Package Level 1 Height	1 in 25 mm	

Package Level 1 Depth / 1 in Length 25 mm

Additional Information	
Application	Stud Mount Transformer Connector
Brand / Label	Homac
Connection Type	Mechanical
Effective Date	20080619
Insulation Material	Insulating Boot
Material	Aluminum
Number of Batteries	0
Number of Conductors	8
Product Name	ELECTRICAL CONNECTOR <1000V
Product Type	Quick-Disconnect Transformer Connector
Special Functions	In-Line Bar Series. Dual Rated for Aluminum and Copper Conductors. High Strength Aluminum Alloy maintains constant bolting pressure on Conductors. Quick Disconnectability for easy removal from transformer secondary studs. Ball-bottom screws ensure maximum conductor contact pressure and break up interstrand oxides.
Standards	ANSI C119.4

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	ABW 8350-1 SLC	
Instructions and Manuals	ABW 8350-1 SLC	

Classifications		
UNSPSC	39121443	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4663 >> Electrical underground bus connector	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Distribution\ Connectors$

