

PRODUCT-DETAILS

## **ABK 4750 C**

## AL TFR Conn 1/0-750 4 Cond



| General Information   |  |
|-----------------------|--|
| Extended Product Type | ABK 4750 C   |
| Product ID            | 7TAA261360R0025  |
| EAN                   | 0783786684175  |
| Catalog Description   | AL TFR Conn 1/0-750 4 Cond   |
| Long Description      | EZ Keeper, Aluminum Transformer Connector, 1/0 - 750 kcmil, Aluminum and Copper, |

| Ordering                |                    |
|-------------------------|--------------------|
| EAN                     | 0783786684175      |
| UPC                     | 783786684175       |
| Country of Origin       | United States (US) |
| Customs Tariff Number   | 8536904000         |
| Selling Unit of Measure | each               |

| Container Information          |                   |
|--------------------------------|-------------------|
| Package Level 1 Units          | 5 piece           |
| Package Level 1 Width          | 8.5 in<br>216 mm  |
| Package Level 1 Height         | 8.5 in<br>216 mm  |
| Package Level 1 Depth / Length | 13.7 in<br>348 mm |

| Additional Information |   |
|------------------------|---|
| Application            | Pad-Mount Tranformer Connector  |
| Brand / Label          | Homac   |
| Connection Type        | Mechanical  |
| Effective Date         | 20080619  |
| Insulation Material    | None  |
| Material               | Aluminum  |
| Number of Batteries    | 0   |
| Number of Conductors   | 4   |
| Product Name           | ELECTRICAL CONNECTOR <1000V   |
| Product Type           | Lay-In Transformer Connector  |
| Size                   | 6-3/16 inch long x 6-47/64 inch wide, Pad 6-47/64 inch x 3-13/16 inch x 9/10<br>inch thick  |
| Special Functions      | Requires only a cable stripper and Allen wrench. No Crimping tools or dies needed. Dual-rated for Aluminum and Copper. Double Set Screws maximize contact area and mechanical characterisitics. Ball-Bottom Screws ensure even force distribution in the cable/connector interface. Transformer changes require only the connector to be unbolted from the spade - no need to disconnect all the conductors, as with compression systems. |
| Standards              | RUS Accepted  |

| Certificates and | Declarations | (Document Num | ber) |
|------------------|--------------|---------------|------|
|------------------|--------------|---------------|------|

| Data Sheet, Technical<br>Information | ABK 4750 C |
|--------------------------------------|------------|
| Instructions and<br>Manuals          | ABK 4750 C |

## Classifications

| Classifications                       |  |
|---------------------------------------|--|
| UNSPSC                                | 39121443                                     |
| WEEE Category                         | Product Not in WEEE Scope                    |
| IDEA Granular Category<br>Code (IGCC) | 4663 >> Electrical underground bus connector |

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Distribution\ Connectors\ Apparatus \rightarrow Distribution\ Apparatus \rightarrow Distribut$ 

