

PRODUCT-DETAILS

# AL 500-38

## ALUM COMP LUG 500 KCMIL 1 HOLE PAD



### General Information

Extended Product Type	AL 500-38
Product ID	7TAA262010R0055
EAN	0783786693894
Catalog Description	ALUM COMP LUG 500 KCMIL 1 HOLE PAD
Long Description	Aluminum Compression Lug for Aluminum and Copper Terminations, One-Hole NEMA Pad, 477-500 kcmil, 600 Compact AL-CU ACSR 397.5 (26/7) and 477 (18/1), Installing Dies 106A, 300, 317, 1 5/16, 14A, 15A. 3/8 inch Bolt. Length 5-7/16 inches, Pad 1-1/2 inch long x 1-3/4 inch wide x 29/64 inch thick. Barrel 2-15/16 inch x 1-5/16 inch Outside Diameter. Oxide Inhibitor. Pink Cap.

### Ordering

EAN	0783786693894
UPC	783786693894
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	1 in 25 mm

Package Level 1 Depth / Length	1 in 25 mm
--------------------------------	---------------

## Additional Information

Application	General Purpose Lugs for Aluminum and Copper Terminations
Brand / Label	Homac
Connection Type	Compression
Effective Date	20080619
Insulation Material	None
Mounting Type	Bolt Size 3/8 in
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL<1000V
Product Type	Compression Lug One Hole
Size	Length 5.437 inches, Pad 1.50 inch long x 1.750 inch wide x .455 inch thick. Barrel 2.938 inches
Special Functions	Dual Rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor. Marked with Conductor Sizes and Die Reference. Meet or Exceed ANSI C119.4 Specifications.
Standards	ANSI C119.4
Wire Size	500 kcmil

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	AL 500-38
Instructions and Manuals	AL 500-38

## Classifications

UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4543 >> Wire connectors

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

