

PRODUCT-DETAILS

# ASL 750 N

## AL 2HOLE NEMA STACK LUG 750



### General Information

Extended Product Type	ASL 750 N
Product ID	7TAA262020R0120
EAN	0783786696642
Catalog Description	AL 2HOLE NEMA STACK LUG 750
Long Description	Aluminum Two-Hole NEMA Lugs - stacking lug, 700-750 kcmil AL-CU, ACSR 636 (26/7), installing dies 140H, 301, 342, 1 1/2. Length 8-1/4 inch. Pad 1-3/4 inch wide x 3 inch long x 7/16 inch thick. (2) 9/16 inch holes on 1-3/4 inch centers. Barrel 3-5/16 inch long x 1-19/32 inch outside Diameter. Oxide Inhibitor. Yellow Cap.

### Ordering

EAN	0783786696642
UPC	783786696642
Country of Origin	United States (US)
Customs Tariff Number	8536904000
Selling Unit of Measure	each

### Container Information

Package Level 1 Units	20 piece
Package Level 1 Width	8.9 in 226 mm
Package Level 1 Height	8.4 in 213 mm

Package Level 1 Depth / Length	13.9 in 353 mm
--------------------------------	-------------------

**Additional Information**

Application	General purpose lugs for Aluminum and Copper terminations.
Brand / Label	Homac
Connection Type	Compression
Effective Date	20080619
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL<1000V
Product Type	Compression Lug Two Hole Stacking
Size	Length 8-1/4 inches X 1-3/4 inch wide
Special Functions	Made from Aluminum which provides high strength and high conductivity. Dual-rated. Use with Aluminum and Copper conductors. Prefilled with oxide inhibitor to prevent oxidation and keep out moisture. All lugs marked with conductor sizes and die reference for easy identification.
Standards	ANSI C119.4
Wire Size	700 to 750 kcmil

**Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	ASL 750 N
Instructions and Manuals	ASL 750 N

**Classifications**

UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4543 >> Wire connectors

**Categories**

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Distribution Connectors

